



KENT P1 - Type 1 IGU

The Kent in Ground Power Unit, **KIGU-400/450 Type 1** is an ideal product for food vendors, outside broadcast units, performers, Christmas tree locations and anywhere that cable clutter needs to be reduced.

The IGU Type 1 contains an IP67 rated electrical panel that can house 1 or 2 16 amp sockets. For added safety the lids can be closed during operation, this setting requires a 450mm depth to allow for plug in space. There is also an option for a shallow unit that has a 320mm depth. However, this depth restricts the unit to use only in the open position.

The recessed cover ensures the units are unobtrusive when not in use. The recessed covers are manufactured in accordance with FACTA and BS EN124 standards. The covers are suitable for 60mm paving blocks and can be customised for 80/100mm. They are fabricated in Grade 316 stainless steel as standard.

- Features**
- ❑ Gas Rams
 - ❑ 2nr IP67 rated sockets as standard
 - ❑ Slam lock
 - ❑ Excellent for market trading areas
 - ❑ 110mm diameter outlet point

- Designed For**
- ❑ 2nr 16 Amp 1 Phase



This box is typically used for access by maintenance crews - Power Washers, Lighting, Monolith Displays, Ticket Sales.

KENT P1 - Type 1 IGU

Product Code	Visible Frame Size	Unit Depth	Cable Duct (Ø)
KIGU 400/450	400mm x 450mm	450mm	125mm

Specify Kent IGU– Type 1; (KIGU 400/450); 400mm x 450mm top ; with a 450mm depth (Closed Use); Grade 316 Stainless Steel; 2nr 16 Amp 1 Phase



44 Ton Truck
FACTA B Loading
EN124 B125 Loading

